



**ESC 60**

## **SAFETY DATA SHEET**

**Issue Date:** 06/12/2023

**Print Date:** 06/12/2023

MAGMAWELD encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

### **1. IDENTIFICATION**

**Product name:** Arc Welding / CELLULOSIC TYPE STICK ELECTRODES– ESC 60

**Recommended use of the chemical and restrictions on use**

**Identified uses:** Arc Welding – CELLULOSIC TYPE STICK ELECTRODE

**COMPANY IDENTIFICATION**

OERLIKON KAYNAK ELEKTRODLARI VE SANAYİ A.Ş.  
ORGANİZE SANAYİ BÖLGESİ 2.KISIM 45010  
YUNUSEMRE MANİSA / TÜRKİYE  
www.magmaweld.com

**Customer Information Number:** (+90) 236 226 26 00

info@magmaweld.com

**EMERGENCY TELEPHONE NUMBER**

**24-Hour Emergency Contact:** 00 90 236 226 26 00

### **2. HAZARDS IDENTIFICATION**

**2.1 Classification of the substance or mixture**

Classification according to EC regulation 1272/2008 (CLP)

This substance is classified as not hazardous.

The product contains titanium dioxide which is possibly carcinogenic .

The product contains quartz ,but not an inhalable form.Quartz can cause silicosis and may cause cancer.

**2.2 Label elements**

**Labelling (CLP)**

**Hazard statements :** not applicable

**Precautionary statements :** not applicable

**2.3 Other Hazards**

These products are normally not considered hazardous as shipped.Gloves should be worn when handling to prevent

cuts or abrasions or possible allergic reactions.

Persons with a pacemaker should not go near welding or cutting operations until they have consulted their doctor and obtained information from the manufacturer of the device.

Electric shock can kill.

Arc ray can severely damage eyes or skin.

Spatter and melting metal can cause burn injuries and start fires.

Formation of dangerous fumes during use. Inhalation of welding fumes may cause respiratory irritation. Cough. Excessive or prolonged inhalation of fumes may cause metal fume fever.

---

---

### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

---

---

This product is a mixture.

Ingredients	CAS NO	EINECS	content	Hazardous classification	H phrases	R phrases
Iron	7439-89-6	231-096-4	70-90	No	No	No
Manganese	7439-96-5	231-105-1	1,00-3,00	No	No	No
Cellulose	9004-34-6	232-674-9	6-9	No	No	No
Iron oxides	1317-60-8	215-168-2	<1	No	No	No
Silicate binder (potassium)	1312-76-1	215-199-1	2-4	No	No	No
Silicate Binder (sodium)	1344-09-8	215-687-4	2-4	No	No	No
Silicon Dioxide	14808-60-7	238-878-4	1-2	H372	Xn	R48/20
Titanium Oxide	13463-67-7	236-675-5	2-5	No	No	No

---

---

### **4. FIRST AID MEASURES**

---

---

#### **Description of first aid measures**

##### **4.1 Description of first aid measures**

**Inhalation :** If breathing is difficult, provide fresh air and call physician. If breathing has stopped, perform artificial respiration and obtain medical assistance immediately.

**Eye contact :** To remove dusts or fumes flush with water for fifteen minutes. If irritation persists, obtain medical assistance. For radiation burns due to arc flash, see physician.

**Skin contact :** For skin burns from arc radiation, promptly flush with cold water. Get medical attention for burns or irritations that persist. To remove dust or particles wash with mild soap and water.

**Electric shock:** Disconnect and turn off the power. Use a nonconductive material to pull victim away from contact with live parts or wires. If not breathing, begin artificial respiration, preferably mouth to mouth. If no detectable pulse, begin Cardio Pulmonary Resuscitation. Immediately call a physician.

**Ingestion:** Rinse mouth. Do not induce vomiting. Obtain emergency medical attention.

##### **4.2 Most important symptoms and effects, both acute and delayed**

Can cause nausea and vomiting

---

**4.3 Indication of any immediate medical attention and special treatment needed**  
*Treat symptomatically .*

---

## **5. FIREFIGHTING MEASURES**

---

### **5.1 Extinguishing media**

The products are not flammable, but welding hot slag or sparks may cause fire. Use extinguishing media recommended for the burning materials and fire situation. Do not enter fire area without proper protective equipment, including respiratory protection.

### **5.2 Special hazards arising from the substance or mixture**

No special hazards

### **5.3 Advice for firefighters**

Wear self-contained breathing apparatus. Wear suitable protective clothing.

### **5.4 Hazchem code**

None allocated .

---

## **6. ACCIDENTAL RELEASE MEASURES**

---

### **6.1 Personal precautions ,protective equipment and emergency procedures:**

Equip clean-up crew with proper protection.

### **6.2 Environmental precautions:**

On land ,sweep or shovel into suitable containers.

### **6.3 Methods and material for containment and cleaning up**

No need

### **6.4 Reference to other sections**

Refer additionally to section 8 and 13

---

## **7. HANDLING AND STORAGE**

---

### **7.1 Precautions for safe handling**

Handle with care to avoid stings and cuts. Wear gloves when handling welding consumables. Avoid exposure to dust. Do not ingest. Some individuals can develop an allergic reaction to certain materials. Retain all warning and identity labels.

### **7.2 Conditions for safe storage , including any incompatibilities**

Keep separate from chemical substances like acids and strong bases, which could cause chemical reactions.

### **7.3 Special end use(s)**

No information available

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

### 8.1 Control Parameters

Exposure standards

Substance	cas no	ACGIH TLV (mg/m3)	OSHA PEL (mg/m3)
Titanium Oxide	134-67-7	10	15*
Manganese	7439-96-5	0,2	5
Iron(as iron oxide)	7439-89-6	5**	10(fume)
Silicon Dioxide	14808-60-7	25**	10 mg/m <sup>3</sup> /(%SiO <sub>2</sub> +2)
Cellulose	9004-34-6	10	15*,5**

\*Total dust \*\*Respirable fraction \*\*\*Inhalable fraction

### 8.2 Exposure controls

Ensure sufficient ventilation,local exhaust,or both ,to keep welding fumes and gases from breathing zone and general area.

Keep working place and protective clothing clean and dry.

Train welders to avoid contact with live electrical parts and insulate conductive parts.

Check condition of protective clothing and equipment on a regular basis.

### Personal protective equipment

Avoid exposure to welding fumes,radiation,spatter,electric shock,heated materials and dust.

In case of insufficient ventilation,wear suitable respiratory equipment.Do not breathe gas,fumes,vapour.

For hand protection, wear welding gloves.

For eye protection ,use a protection mask equipped with suitable filter glasses.Interdiction to wear contact lenses.

For body protection,use suitable clothing,helmet,boots.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

### 9.1 Information on basic physical and chemical properties

Appearance :Solid,non-volatile with varying color

Odour: Odourless

Density(kg/lit) : 7,8

pH value : Not applicable

Melting Point (0C) : ca 1500

Flashing point :not applicable

Auto Ignition Temperature : Not applicable

Explosion Limits : . Not applicable

Solubility in water :Insoluble

Viscosity : Not applicable

### 9.2 Other information

Not relevant

NOTE: The physical data presented above are typical values and should not be construed as a specification.

---

---

## **10. STABILITY AND REACTIVITY**

---

### **10.1 Reactivity**

These products are stable under normal conditions..

### **10.2 Chemical stability**

Contact with chemical substances like acids or strong bases could cause generation of gas.

### **10.3 Possibility of hazardous reactions**

Formation of dangerous fumes during use.Welding fumes are classified carcinogen by the IARC (International Agency for Research on Cancer):Group 2B Cancer suspected agent.

### **10.4 Conditions to avoid**

Reasonably expected gaseous products would include carbon oxides,nitrogen oxides and ozone.Air contaminants around the welding area can be affected by the welding process and influence the composition and quantity of fumes and gases produced.

The amount of fumes generated from these products varies with welding parameters and dimensions.Fumes from these products may contain compounds of the following chemical elements:Fe,O,Mn,Zr,Si,Al,Cu,C,and Ti.

### **10.5 Incompatible materials**

Incompatible with acids and bases

### **10.6 Hazardous decomposition products**

Fumes from these products may contain compounds of the following chemical elements:Fe,O,Mn,Zr,Si,Al,Cu,C,and Ti.

---

---

## **11. TOXICOLOGICAL INFORMATION**

---

### **11.1 Information on toxicological effects**

#### **Acute toxicity**

No known toxicological effects from this product

#### **Skin**

Not classified as irritating to the skin . Contact may result in mechanical irritation.

#### **Eye**

Contact may result in mechanical irritation.

#### **Sensitisation**

Inhalation of welding fumes and gases can be dangerous to your health .Classification of welding fumes is difficult because of varying base materials,coatings,air contamination and process.IARC (International Agency for Research on Cancer)has classified welding fumes as possibly carcinogenic to humans (Group 2B)

Acute Toxicity:Overexposure to welding fumes may result in symptoms like metal fume fever ,dizziness,nausea,dryness or irritationof nose,throat or eyes.

Chronic Toxicity:Overexposure to welding fumes may affect pulmonary function.Overexposure to manganese and manganese compounds above safe exposure limits can cause irreversible damage to the central nervous system ,including the brain,symptoms of which may include slurred speech ,lethargy,tremor,muscular weakness,psychological

disturbances and spastic gait.

**Mutagenicity**

No evidence of mutagenic effects

**Carcinogenicity**

Inhalation of welding fumes and gases can be dangerous to your health .Classification of welding fumes is difficult because of varying base materials,coatings,air contamination and process.IARC (International Agency for Research on Cancer)has classified welding fumes as possibly carcinogenic to humans (Group 2B)

**Reproductivity**

No evidence of reproductive effects

**STOT-single exposure**

Not relevant

**STOT-repeated exposure**

Not relevant

**Aspiration**

Overexposure to welding fumes may affect pulmonary function.Overexposure to manganese and manganese compounds above safe exposure limits can cause irreversible damage to the central nervous system ,including the brain,symptoms of which may include slurred speech ,lethargy,tremor,muscular weakness,psychological disturbances and spastic gait.

---

---

## **12. ECOLOGICAL INFORMATION**

---

**12.1 Toxicity**

No data available

**12.2 Persistence and degradability**

No data available

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

No data available

**12.6 Other adverse effects**

None

Avoid release to the environment .Do not discharge in sewer.

---

---

## **13. DISPOSAL CONSIDERATIONS**

---

**13.1 Waste treatment methods**

Welding process disposals can accumulate in soil and underground water paths.

Slugs can contain Fe,Mn,Si,Ti,Al,Mo,Zr and Cu oxides and compounds.

Dispose in a safe manner in accordance with local/national regulations.Use recycling procedures if available.

---

---

## 14. TRANSPORT INFORMATION

---

### 14.1 UN number

Not applicable

### 14.2 UN proper shipping name

Not restricted

### 14.3 Transport hazard class(es)

Not applicable

### 14.4 Packing group

Not applicable

### 14.5 Environmental hazards

No

### 14.6 Special precautions for user

No dangerous good in sense of these transport regulations

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No available data

No international regulations or restrictions are applicable.

---

---

## 15. REGULATORY INFORMATION

---

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Classification of substance and mixtures, labeling and packaging regulation

### 15.2 Chemical safety assessment

No data available

---

---

## 16. OTHER INFORMATION

---

### Product Literature

Additional information on this and other products may be obtained by visiting our web page.

### Revision

Issue Date: 11/04/2016 / Version: 1.0

### Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
TWA	8-hour, time-weighted average

### Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

MAGMAWELD urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer- specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.