

## Manufacturer's Instructions and Information

**Sample Description:** 13G UHMWPE/glass fibre/steel/polyester/spandex liner with PU palm coating

**Product Style/Order No:** P3845/6, P3845/7, P3845/8, P3845/9, P3845/10, P3845/11

**Product code/colour:** black

### Risks against which the PPE is intended to protect:


The gloves are employed and intended to protective against mechanical risks of abrasion, TDM cut, tear, puncture of palm in working environment.

The gloves meet the requirement for resistance to puncture, may not be suitable for protection against sharply pointed objects such as hypodermic needles.


The gloves are not to be used for chemical protection, naked flame, electrical protection or use where a risk of entanglement by moving parts.

The composition of gloves do not contain substances which are known to cause allergies

Risk	Standard Clause	Assessment method
Abrasion	EN 388:2016+A1:2018 Clause 6.1	Abrasion resistance numbers of rubs
Cut	EN 388:2016+A1:2018 Clause 6.3	Cut resistance strength
Tear	EN 388:2016+A1:2018 Clause 6.4	Tear resistance strength
Puncture	EN 388:2016+A1:2018 Clause 6.5	Puncture resistance strength

 This product has been labelled with a CE mark in conformity with the provisions of Module B of the Regulation (EU) 2016/425 Personal Protective

### Pictograms and Performance Levels of certified gloves:

EN 388: 2016+A1:2018	Performance	Performance levels
 4X43D	Abrasion resistance	Level 4
	Blade cut level	X
	Cut resistance (EN 13997)	Level D
	Tear resistance level	Level 4

	Puncture resistance	Level 3
	Impact protection	blank
X: indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material		

**Interpretation of the levels of performance (according to EN 388:2016+A1:2018)**

Test	Level 1	Level 2	Level 3	Level 4	Level 5	
6.1 Abrasion resistance (number of rubs)	100	500	2 000	8 000	-	
6.4 Tear resistance (N)	10	25	50	75	-	
6.5 Puncture resistance (N)	20	60	100	150	-	
	Level A	Level B	Level C	Level D	Level E	Level F
6.3 TDM: cut resistance (N)	2	5	10	15	22	30

**Storage:** Always store in clean, dry conditions. Do NOT store in places subject to direct, strong sunlight.

**Available Sizes & Selection:**

Fit according to hand size Allowance built in for comfort. Check the fit before using in working conditions

Unit: mm

Glove size	Hand length	Hand circumference
6	<160	168
7	160	174
8	171	182
9	182	194
10	192	204
11	204	210

**Limitations of Use:**

Safety required only if the right size of the gloves is used and applied. Please check any damage before using. The special features may be restricted or even lost if it is excessive dirty and damaged, please replace it with a new glove. The life time of the gloves is 5 years.

**Warning:**

The gloves are not to be used for chemical protection, naked flame, electrical protection or use where a risk of entanglement by moving parts. The gloves meet the requirement for resistance to puncture, may not be suitable for protection against sharply pointed objects such as hypodermic needles. The gloves cannot be washed.

**Disposal:** Follow local disposal rule

**Aftercare:** The glove is not washable.

**Manufacturer:** Parweld Ltd

Address: Bewdley business Park, long bank, Bewdley Worcestershire DY12 2TZ, United Kingdom

EU & UK declaration of conformity can be accessed at: [https://parweld.info/document/p3845-panther-pu-cut-d\\_doc\\_en](https://parweld.info/document/p3845-panther-pu-cut-d_doc_en)

Detailed content of the Instructions and information notice is the responsibility for manufacture

**Made in China**

EU type-examination for Regulation (EU) 2016/425 by

Notified Body Number: 0598

SGS Fimko Oy, Takomotie 8, FI-00380 Helsinki, Finland.

UK type-examination for Regulation 2016/425 on personal protective equipment as brought into UK law and amended by

SGS United Kingdom Limited,

Approved Body Number: 0120

Rossmore Business Park, Ellesmere Port, South Wirral, Cheshire, CH65 3EN, United Kingdom.