

Certificate Number: XP-02093

Customer: Reinsol Soldaduras Y Mantenimiento
Camino del Bony, 55 Pol. Ind. Catarroja, 46470
Catarroja, Valencia, Spain

Order Number: 254

Quantity Purchased: 250 kg

Lot Number: 242518915

EN/ISO Standards: 14343-A
EN/ISO Classification: W 19 12 3 L
DIN Standard: A5.9
DIN Classification: ER316L

Item Number: XP30368
Description: XP 316L
Dimensions: Ø 1.6 x 1000 (mm)
Packaging / Weight: Tube - 5kg

Chemical Composition

According to EN 10204:2004 - 3.1

| Elements | Test Result % (m/m) | Elements | Test Result % (m/m) |
|----------|---------------------|----------|---------------------|
| C | 0.023 | - | - |
| Si | 0.49 | - | - |
| Mn | 1.61 | - | - |
| P | 0.025 | - | - |
| S | 0.013 | - | - |
| Cr | 18.17 | - | - |
| Ni | 11.05 | - | - |
| Mo | 2.53 | - | - |
| Cu | 0.19 | - | - |
| N2 | 0.0440 | - | - |
| - | - | - | - |

Mechanical Properties

According to EN 10204:2004 - 3.1

| | Test Result |
|-------------------------|-------------|
| Tensile Strength (MPa) | 628 |
| Yield Strength (MPa) | 470 |
| Elongation (%) | 36 |
| Impact Strength (J) | 102 |
| Ferrite (FN) Indicative | 9 |
| Test Temperature (°C) | - |

We hereby certify that this report is correct and all results are in conformity with the declared specifications described herein.

Jason Ford - Product Manager

City: Bewdley, Worcestershire

Date: 07/11/2024

This digitally prepared certificate is valid without signature



Remarks:

Scan to Download

